WHITE LIMBA

Terminalia superba





WOOD DESCRIPTION

Color: Light yellow
Sapwood: Not Demarcated

Texture: Medium

Grain: Straight or Interlocked

CHARACTERISTICS

- Easy to work
- Not Durable
- Susceptible to termites

COMMON USES

- Cabinetwork
- Moulding
- Sliced veneer
- Paneling (interior / exterior)
- Joinery (interior / exterior)
- Rolling shutters
- Cigar boxes
- Light carpentry

AVAILABILITY

- Select & Better
- Mixed Grain
- 4/4 Thickness

PHYSICAL / MECHANICAL PROPERTIES

Air Dry Density	2.9 lbs/bf
Specific Gravity:	0.56
Janka Hardness (lbs):	670
Volumetric Shrinkage:	10.8%
Total Tangential Shrinkage (TS):	6.1%
Total Radial Shrinkage (RS):	4.3%
TS/RS Ratio:	1.4

Fiber Saturation Point:	28%
Crushing Strength:	6,816 lbf
Static Bending Strength:	11,603 lbf
Modulus of Elasticity:	1,704,193 lbf
Stability:	Moderate

WORKING PROPERTIES

Blunting Effect:	Normal
Sawteeth Recommended:	Ordinary / Alloy Steel
Cutting Tools:	Ordinary
Peeling:	Good

Slicing:	Good
Nailing / screwing:	Good
Gluing:	Good